



Seed Lube #3 – Seed Lubricant

Seed Lube #3 is a very fine, high purity Talc / Graphite blended powder designed to eliminate bridging inside the planter box. Talc by nature is an inert material that will not effect the seed, soil or environment, graphite adds additional lubrication values to the mix. Seed Lube #3 (Talc/Graphite) is ideal for use on newer style air planters when heavy seed treatment is present. The Talc will coat the seeds in the planter box and the graphite aids in lubricating the planter box side walls, also reducing equipment wear. Seed Lube #3 is not recommended for use on the older style finger planters. Seed Lube #1 is better suited for those applications.

Customer Benefits

- **No Bridging** –Seed Lube #3 works as a non stick coating, aiding in seed separation in the planter box
- **Higher Crop Yields** – Seed Lube #3 dramatically increases the planters consistency of laying down evenly placed, single seeds.
- **Extended Machinery Life** – By reducing harmful abrasives from sticking and the low coefficient of friction values, equipment runs smoother and lasts longer.
- **Reduced Maintenance** – Trouble free operation of equipment and extended maintenance intervals.
- **Reduced Cost** – Since Seed Lube #3 helps reduce seeds sticking together, you can plant faster and with higher efficiency.

Applications

Planter Equipment

Specifications

Type	Powder
Lubricant	Talc / Graphite
Carrier	NA
Consistency	Very Fine Powder
AVG. PARTICAL SIZE	Proprietary
Total Solids	100%
Available Size	7 lb., 12 lb. and custom packaging

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products. ©2006 All rights reserved.

Visit <http://www.acrolube.com> for Material Safety Data Sheets (MSDS) and further product information.

Acrotech Industries, Inc. 4503 Ray St. Crystal Lake, IL. 60012 PH: (815) 788-8891 FAX: (815) 788-8893